Certificate Number UL-US-2016790-4

Report Reference E199779-20200811

Date 28-Aug-2023

Issued to: ARCH ELECTRONICS CORP

3F No 79 Sec 1 Hsin Tai Wu Rd

Hsi Chih District New Taipei 221

Taiwan

This is to certify that representative samples of

QQJQ2 - Power Supplies for Use with Audio/Video, Information and Communication Technology Equipment -Component

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete

in certain constructional features or restricted in

performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.

Standard(s) for Safety: UL 62368-1, 2nd Ed., Issue Date: 2014-12-01

Additional Information: See the UL Online Certifications Directory at

https://ig.ulprospector.com for additional information

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Recognized Component Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.

Deborah Jennings-Conner, VP Regulatory Services

Which Jenning - Cress

UL LLC



Certificate Number UL-US-2016790-4

Report Reference E199779-20200811

Date 28-Aug-2023

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements

Model	Category Description
AQF240E-12S24S	Switching Power Supply
ARCHTCI240-x1Ax2YYYYYYY, (where "x1" can be 109	Switching Power Supply
to 112.48, 118 to 124.96 or 136 to 149.92, "x2" can be –	
J or -T, and "Y" can be 0-9, a-z, A-Z, - or blank)	
ARCHTCl240-x1Ux2YYYYYYY, (where "x1" can be 109	Switching Power Supply
to 112.48, 118 to 124.96 or 136 to 149.92, "x2" can be –	
J or -T, and "Y" can be 0-9, a-z, A-Z, - or blank)	
ARCHTCl240-x1x2YYYYYYY, (where "x1" can be 109 to	Switching Power Supply
112.48, 118 to 124.96 or 136 to 149.92, "x2" can be –J	
or -T, and "Y" can be 0-9, a-z, A-Z, - or blank)	LTVLTVLTVLTVLT
ARF240E-xSYYYYYYY, x can be 9 to 12.48, 18 to 24.96	Power Supplies for AV, ITE, and AVICT
or 36 to 49.92 and Y can be 0-9, a-z, A-Z, - or blank	Equipment
ARF240O-xSYYYYYYY, x can be 9 to 12.48, 18 to 24.96	Power Supplies for AV, ITE, and AVICT
or 36 to 49.92 and Y can be 0-9, a-z, A-Z, - or blank	Equipment
ARF240U-xSYYYYYYY, x can be 9 to 12.48, 18 to 24.96	Power Supplies for AV, ITE, and AVICT
or 36 to 49.92 and Y can be 0-9, a-z, A-Z, - or blank	Equipment
ARFV240E-xSYYYYYYY, (where "x" can be 9 to 12.48,	Switching Power Supply
18 to 24.96 or 36 to 49.92 and "Y" can be 0-9, a-z, A-Z, -	
or blank)	$- \sum_{i} \sum_{j} \sum_{j} \sum_{i} \sum_{j} \sum_{j} \sum_{i} \sum_{j} \sum_{j} \sum_{i} \sum_{j} \sum_$
ARFV240O-xSYYYYYYY, (where "x" can be 9 to 12.48,	Switching Power Supply
18 to 24.96 or 36 to 49.92 and "Y" can be 0-9, a-z, A-Z, -	
or blank)	\wedge
ARFV240U-xSYYYYYYY, (where "x" can be 9 to 12.48,	Switching Power Supply
18 to 24.96 or 36 to 49.92 and "Y" can be 0-9, a-z, A-Z, -	
or blank)	
MQC100-xSYYYYYYY, x can be 9 to 12.48, 18 to 24.96	Power Supplies for AV, ITE, and AVICT
or 36 to 49.92 and Y can be 0-9, a-z, A-Z, - or blank	Equipment
MQC150-xSYYYYYYY, x can be 9 to 12.48, 18 to 24.96	Power Supplies for AV, ITE, and AVICT
or 36 to 49.92 and Y can be 0-9, a-z, A-Z, - or blank	Equipment
MQF240E-xSYYYYYYY, x can be 9 to 12.48, 18 to	Power Supplies for AV, ITE, and AVICT
24.96 or 36 to 49.92 and Y can be 0-9, a-z, A-Z, - or	Equipment
blank	
MQF240O-xSYYYYYYY, x can be 9 to 12.48, 18 to	Power Supplies for AV, ITE, and AVICT
24.96 or 36 to 49.92 and Y can be 0-9, a-z, A-Z, - or	Equipment
blank	シーケーケーケーケー
MQF240U-xSYYYYYYY, x can be 9 to 12.48, 18 to	Power Supplies for AV, ITE, and AVICT
24.96 or 36 to 49.92 and Y can be 0-9, a-z, A-Z, - or	Equipment
blank	

Octroh Jenning-Come-

(L)

eborah Jennings-Conner, VP Regulatory Services

Certificate Number Report Reference

UL-CA-2013367-4 E199779-20200811

Date

28-Aug-2023

Issued to:

ARCH ELECTRONICS CORP 3F No 79 Sec 1 Hsin Tai Wu Rd

Certified for Canada - Component

Hsi Chih District New Taipei 221

Taiwan

This is to certify that representative samples of

QQJQ8 - Power Supplies for Use with Audio/Video, Information and Communication Technology Equipment

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete

in certain constructional features or restricted in

performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.

Standard(s) for Safety:

CSA C22,2 No. 62368-1-14, 2nd Ed., Issue Date: 2014-12-

01

Additional Information:

See the UL Online Certifications Directory at

https://ig.ulprospector.com for additional information

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Recognized Component Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.

Deborah Jennings-Conner, VP Regulatory Services

Which Jennings - Com

UL LLC



 Certificate Number
 UL-CA-2013367-4

 Report Reference
 E199779-20200811

 Date
 28-Aug-2023

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements

Model	Category Description
AQF240E-12S24S	Switching Power Supply
ARCHTCl240-x1Ax2YYYYYYY, (where "x1" can be 109	Switching Power Supply
to 112.48, 118 to 124.96 or 136 to 149.92, "x2" can be –	イレグストゲストゲストゲストゲ
J or -T, and "Y" can be 0-9, a-z, A-Z, - or blank)	
ARCHTCl240-x1Ux2YYYYYYY, (where "x1" can be 109	Switching Power Supply
to 112.48, 118 to 124.96 or 136 to 149.92, "x2" can be -	J1 30 U1 30 U1 30 U1 30 U1 30 U1 30 U
J or -T, and "Y" can be 0-9, a-z, A-Z, - or blank)	
ARCHTCl240-x1x2YYYYYYY, (where "x1" can be 109 to	Switching Power Supply
112.48, 118 to 124.96 or 136 to 149.92, "x2" can be –J	L VIII. VIII. VIII. VIII. VIII. VI
or -T, and "Y" can be 0-9, a-z, A-Z, - or blank)	プレスアレスアレスアレスアレス
ARF240E-xSYYYYYYY, x can be 9 to 12.48, 18 to 24.96	Power Supplies for AV, ITE, and AVICT
or 36 to 49.92 and Y can be 0-9, a-z, A-Z, - or blank	Equipment
ARF240O-xSYYYYYYY, x can be 9 to 12.48, 18 to 24.96	Power Supplies for AV, ITE, and AVICT
or 36 to 49.92 and Y can be 0-9, a-z, A-Z, - or blank	Equipment
ARF240U-xSYYYYYYY, x can be 9 to 12.48, 18 to 24.96	Power Supplies for AV, ITE, and AVICT
or 36 to 49.92 and Y can be 0-9, a-z, A-Z, - or blank	Equipment
ARFV240E-xSYYYYYYY, (where "x" can be 9 to 12.48,	Switching Power Supply
18 to 24.96 or 36 to 49.92 and "Y" can be 0-9, a-z, A-Z, -	
or blank)	
ARFV240O-xSYYYYYYY, (where "x" can be 9 to 12.48,	Switching Power Supply
18 to 24.96 or 36 to 49.92 and "Y" can be 0-9, a-z, A-Z, -	
or blank)	
ARFV240U-xSYYYYYYY, (where "x" can be 9 to 12.48,	Switching Power Supply
18 to 24.96 or 36 to 49.92 and "Y" can be 0-9, a-z, A-Z, -	ピレスアレスアレスアレスアレス
or blank)	
MQC100-xSYYYYYYY, x can be 9 to 12.48, 18 to 24.96	Power Supplies for AV, ITE, and AVICT
or 36 to 49.92 and Y can be 0-9, a-z, A-Z, - or blank	Equipment
MQC150-xSYYYYYYY, x can be 9 to 12.48, 18 to 24.96	Power Supplies for AV, ITE, and AVICT
or 36 to 49.92 and Y can be 0-9, a-z, A-Z, - or blank	Equipment
MQF240E-xSYYYYYYY, x can be 9 to 12.48, 18 to	Power Supplies for AV, ITE, and AVICT
24.96 or 36 to 49.92 and Y can be 0-9, a-z, A-Z, - or	Equipment
blank	
MQF240O-xSYYYYYYY, x can be 9 to 12.48, 18 to	Power Supplies for AV, ITE, and AVICT
24.96 or 36 to 49.92 and Y can be 0-9, a-z, A-Z, - or	Equipment
blank	3/ 5/ 5/ 5/ 5/
MQF240U-xSYYYYYYY, x can be 9 to 12.48, 18 to	Power Supplies for AV, ITE, and AVICT
24.96 or 36 to 49.92 and Y can be 0-9, a-z, A-Z, - or	Equipment
blank	「L人~L人~L人~L人~L人~L人)



